

# Comparison of applications of products

#### **Plastering**

### Thin Plastering / Skim Coat

### **Special Repair**

### **Construction Chemicals**















1







/







	CP001	CP105	CP003	CPO15/A	CP051	CP015/K	CPO15/B	CP015/L	CP046/E	CP046/E1	DB-77	DS-22	DW201
Type of product			Plastering Mortar for Concrete Block	Skim Coat (White)	Skim Coat (Grey)	Skim Coat (Light Grey)	Super Skim Coat (White)	Loft Cement for Decoration	Crack Repair Mortar (With Sand)	Crack Repair Mortar (Without Sand)	Bonding Agent Latex	Water Repellent Semi-Gloss	Flexible Waterproofing Cement 2K
Wall material													
Lightweight block	1												
White block, General block, Red block	/	1	<b>/</b>										
Concrete structure			<b>✓</b>										
Wall surface													
Fixing coarse-grained, uneven, wavy wall, hairline crack				<b>✓</b>	1	✓	<b>4</b>	<b>✓</b>					
Bare cement wall, concrete wall				<b>✓</b>	1	✓	<b>✓</b>	<b>✓</b>	<b>~</b>	<b>✓</b>		<b>/</b>	
Prefabricated wall (Precast, Wall panel, Tunnel form)	k			<b>✓</b>	<b>✓</b>	1	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>		<b>/</b>	
Soft wall (fiber cement, gypsum board, cement board)	•			<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	1	<b>✓</b>	<b>✓</b>			
Painted wall (modification), old wall	•						<b>✓</b>	1	<b>✓</b>	<b>✓</b>			
Indoor and outdoor plastered wall	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>/</b>	<b>✓</b>	<b>✓</b>	<b>/</b>

Bonding Primer / Waterproofing							
Bonding between old concrete and new concrete						1	
Waterproofing							<b>/</b>
bathrooms, kitchens, balconies, decks and swimming pools						<b>✓</b>	1

1



Other

Repair

For use with mortar sprayers

For use with mortar mixers

For use with skim coat sprayer



<sup>\*</sup>Basic repair, \*\*Repairing and preventing cracks, \*\*\*Surface finishing for formwork joints



# Comparison of applications of products

#### Mansory

## Tile Adhesive

### Flooring and Leveling



















Jouls

usest

undstuschtwu
entwent his eu

Melance
Molekoo

Type of product				5 5	6					D D : 1	N. Chile	Face Flags Coursed
Lightwages black   Corner lock, Red black	Type of product		Masonry Mortar for General Block					Premium cement grout	Floor Leveling Mortar	Dry Premixed Concrete	Non - Shrink Grout	Easy Floor Screed
With a Back (General Bode). And Bode)  How revising  How revising  How revising a provider connected unforced concrete polaring contenting tennets  Social works such as resolutioned concrete polaring contenting tennets  Social works such as growing connecting tennets and social plate base for machine installation and social column base.  This per leveling for number table, formatic progress, etc.  ***********************************	Wall material											
Floor Investing Support and initial such as reinforced concrete flashing, countertop, tomace  Social works such as quoting concrete surface, leaving percent concrete column base, leaving not such as quoting concrete surface, leaving percent concrete column base.  This layer flowing for maker in the Javanuse, parquate, concrete such percent into the Javanuse, parquate, concrete such formation installation and steel column base.  ****  ****  ***  ****  ***  ***  **	Lightweight block	1										
Contenting	White block, General block, Red block		1									
Ligament and linied such as reinforced concrete flashing, countertup, torrace  \$\frac{1}{2}Special what auch as grouting concrete surface, leveling present confurn bears to be surface for makine initialation and steel column bear    \text{This layer leveling for rubber list, laminate, parquet, etc.	Floor											
Special works such as grazining cancerte surface, leveling procest concrete calumn base, leveling calumn	Floor leveling								1			
Column based for beam support, loveling steel glates base for machine installation and steel column based	Ligament and lintel such as reinforced concrete flashing, countertop, terrace									1		
Column Index for Deem support, Ivening steel plate base for machine installation and steel column base	Special works such as grouting concrete surface, leveling precast concrete column base, leveling concrete											
Trace to 18. mosts, ceans tile (normal water absorption)  **	column head for beam support, leveling steel plate base for machine installation and steel column base										•	
Terracotta tile, moraic, ceramic tile (normal water absorption)   **   **   **   **   **   **   **	Thin layer leveling for rubber tile, laminate, parquet, etc.											1
New Control (No. No. No. No. No. No. No. No. No. No.	Tiles											
Machine, granter (for interior wall and floor covering)  Machine, granter (for interior wall and floor cover	Terracotta tile, mosaic, ceramic tile (normal water absorption)	**		**	***	***	***					
Natural stance	Porcelain tile, Granito (low water absorption)	**		**	***	***	***					
	Marble, granite (for interior wall and floor covering)				**	***	***					
Tiles Sizes  Small : SXISE - 45XIS cm.  **	Natural stone					**	***					
Small : 15x15 - 45x45 cm         *** <td>Glass mosaic, Resin mosaic</td> <td></td> <td></td> <td></td> <td></td> <td>**</td> <td>***</td> <td></td> <td></td> <td></td> <td></td> <td></td>	Glass mosaic, Resin mosaic					**	***					
Medium : 60x60 cm.  Axx	Tiles Sizes											
Large: 90x90 cm, 60x80 cm, 60x120 cm.  Extra large: 100x100 cm.  Super Extra: 100x150 cm.  Area  No need to immerse the tiles in water before installation  ***  ***  ***  ***  ***  ***  ***	Small : 15x15 - 45x45 cm.	**		***	***	***	***					
Extra large : 100x100 cm.  Super Extra : 100x150 cm.  Area  Area  No need to immerse the tiles in water before installation  ***  ***  ***  ***  ***  ***  ***	Medium : 60x60 cm.	**		**	***	***	***					
	Large : 90x90 cm., 60x80 cm., 60x120 cm.			**	***	***	***					
Area  No need to immerse the tiles in water before installation  ***  ***  ***  ***  ***  ***  ***	Extra large : 100x100 cm.					**	***					
No need to immerse the tiles in water before installation         ***	Super Extra : 100x150 cm.						***					
March   Marc	Area											
Indoor wall Outdoor floor Outdoor good  **********************************	No need to immerse the tiles in water before installation	***		***	***	***	***					
Outdoor floor         *         **         ***	Indoor floor	**		**	***	***	***					
Outdoor wall  * ** ** ***  Swimming pool  * ** ** ***  Special surface  ***  ***  ***  ***  ***  ***  ***	Indoor wall			**	***	***	***					
Swimming pool	Outdoor floor			*	**	***	***					
Spcial surface  Tiling over existing tile  Fiber cement board, Cement board, Structural plywood  Gypsum board  Cement Grout  Grout line width: 1-6 mm.  Prevents and inhibits black mold	Outdoor wall			*	**	***	***					
Tiling over existing tile  Fiber cement board, Cement board, Structural plywood  Sypsum board  Cement Grout  Grout line width: 1-6 mm.  Prevents and inhibits black mold	Swimming pool					***	***					
Fiber cement board, Cement board, Structural plywood  Gypsum board  Cement Grout  Grout line width: 1-6 mm.  Prevents and inhibits black mold	Spcial surface											
Gypsum board   Cement Grout   Grout line width: 1-6 mm.   Prevents and inhibits black mold    ***  ***  **  **  **  **  **  **  **	Tiling over existing tile						***					
Cement Grout           Grout line width: 1-6 mm.         ★★★           Prevents and inhibits black mold         ★★	Fiber cement board, Cement board, Structural plywood						***					
Grout line width: 1-6 mm.         ★★★           Prevents and inhibits black mold         ★★	Gypsum board						***					
Prevents and inhibits black mold ★★	Cement Grout											
	Grout line width: 1-6 mm.							***				
Reduces water leakage, the cause of the fungus. ★★	Prevents and inhibits black mold							**				
	Reduces water leakage, the cause of the fungus.							**				



**★** Fair ★★ Good ★★★ Excellent